



SPECTRO



Real Magic Technology Sdn. Bhd. (712397-X)

Real Magic Distribution Sdn. Bhd. (840742-U)

24~30, Jalan Tambun Indah 1, 14100 Simpang Ampat, Penang. Malaysia.

Tel: (+604) 588 9988, 588 9788, 587 3166 Fax: (+604) 588 9912

Spectrology Industry Sdn. Bhd. (869318-U)

Spectro Farmings Sdn. Bhd. (1043775-D)

Spectrology Industry Sdn. Bhd., Zhongshan Rep. Office


www.realmagic-tech.com




NEW

For the "LED world"


Hi-Efficient LED Panel-light 2 sided/ 高效节能 LED 平板灯-2侧面




(300mm x 300mm)



(300mm x 600mm)



(300mm x 1200mm)



(600mm x 1200mm)

Hi-Efficient LED Panel-light specifications (高效节能 LED 平板灯产品参数):

Product Specifications (产品参数)	LED-2P12-S303 (Frosted)	LED-2P24-S306 (Frosted)	LED-2P48-S312 (Frosted)	LED-2P48-S612 (Frosted)	Tolerances (公差)
Power rating/功率 (W):	12W	24W	48W	48W	± 10%
Current/电流 (A) @ 240Vac:	≤ 0.060 A	≤ 0.130 A	≤ 0.250 A	≤ 0.250 A	± 10%
Voltage/交流电压 (V):	AC 220V ~ 240V				± 10%
Power factor/功率因数 (pf):	≥ 0.90				± 0.03
Holder type/灯头座:	Internal Driver as specifications				
Opr. temperature/工作温度 (°C):	-10°C ~ 50°C				± 2°C
Dimensions/尺寸规格 (mm):	300x300xH13	300x600xH13	300x1200xH13	600x1200xH13	± 2%
Luminous Flux/光通量 (Lm):	≥ 750, 180°	≥ 1500, 180°	≥ 3000, 180°	≥ 3000, 180°	± 5%
Color Temperature/色温 (K):	6500K / 5000K / 3000K				± 5%
CRI (Ra) / 显色 (%):	≥ 72				± 1%
Mercury (Amalgam)/汞含量 (mg):	NIL				
Electronic lifespan/电器寿命:	≥ 40k hrs (小时)				
Certifications/认证:	Electrical/电器: CE				3 rd party
Warranty/质保期 (months/月):	24mths on selected products / 选择性产品, 24个月				

NOTE: The above data is for product references, and REAL MAGIC has the right to make changes without notice.

注: 以上为产品数据参考, REAL MAGIC 拥有无条件更改参数权。



SPECTRO



Real Magic Technology Sdn. Bhd. (712397-X)

Real Magic Distribution Sdn. Bhd. (840742-U)

24~30, Jalan Tambun Indah 1, 14100 Simpang Ampat, Penang. Malaysia.

Tel: (+604) 588 9988, 588 9788, 587 3166 Fax: (+604) 588 9912

Spectrology Industry Sdn. Bhd. (869318-U)

Spectro Farmings Sdn. Bhd. (1043775-D)

Spectrology Industry Sdn. Bhd., Zhongshan Rep. Office


www.realmagic-tech.com




NEW

For the "LED world"


Hi-Efficient LED Panel-light 4 sided/ 高效节能 LED 平板灯-4侧面 (Super thin 12.5mm)




(300mm x 300mm)



(300mm x 600mm)



(600mm x 600mm)



(600mm x 1200mm)

Hi-Efficient LED Panel-light specifications (高效节能 LED 平板灯产品参数):

Product Specifications (产品参数)	LED-4P24-S303 (Frosted)	LED-4P36-S306 (Frosted)	LED-4P48-S606 (Frosted)	LED-4P72-S612 (Frosted)	Tolerances (公差)
Power rating/功率 (W):	24W	36W	48W	72W	± 10%
Current/电流 (A) @ 240Vac:	≤ 0.130 A	≤ 0.180 A	≤ 0.250 A	≤ 0.360 A	± 10%
Voltage/交流电压 (V):	AC 220V ~ 240V				± 10%
Power factor/功率因数 (pf):	≥ 0.90				± 0.03
Holder type/灯头座:	Internal Driver as specifications				
Opr. temperature/工作温度 (°C):	-10°C ~ 50°C				± 2°C
Dimensions/尺寸规格 (mm):	300x300xH12.5	300x600xH12.5	600x600xH12.5	600x1200xH12.5	± 2%
Luminous Flux/光通量 (Lm):	≥ 1500, 180°	≥ 2200, 180°	≥ 3000, 180°	≥ 4500, 180°	± 5%
Color Temperature/色温 (K):	6500K / 5000K / 3000K				± 5%
CRI (Ra) / 显色 (%):	≥ 72				± 1%
Mercury (Amalgam)/汞含量 (mg):	NIL				
Electronic lifespan/电器寿命:	≥ 40k hrs (小时)				
Certifications/认证:	Electrical/电器: CE				3 rd party
Warranty/质保期 (months/月):	24mths on selected products / 选择性产品, 24个月				

NOTE: The above data is for product references, and REAL MAGIC has the right to make changes without notice.

注: 以上为产品数据参考, REAL MAGIC 拥有无条件更改参数权。